

**REMARKS**

This is in full and timely response to the Final Action dated September 22, 2005. A Notice of Appeal was timely filed on February 22, 2006. This paper accompanies an RCE that is timely filed with a Petition to Extend the Time for Response to Within the Fourth Month. Thus, this RCE is timely.

**Rejection of Claims 16 to 20 under 35 USC 103**

The claims submitted are those at Final Action. In that paper, the examiner had rejected claims 16 to 20 as unpatentable over Richmond '170 in view of Nixon '784 and further in view of Bologovsky et al. The examiner had taken Official Notice that it is well known to employ thermo-welding as a bonding means; a citation to that effect is respectfully requested.

It is noted that there are no findings of fact on which to base a motivation or impetus to combine the teachings of the references, even if the Richmond device were available as a reference. To the extent, for example, that Nixon does a pair of mating board portions, there is no teaching that it was intended in Nixon to provide a body board with an outer plastic shell as alleged which prevents absorption of blood. Furthermore, the sealing alleged to be found in Bologovsky is not directed to a combination having features as alleged; indeed Bologovsky is not directed to sealing to reduce a likelihood that the interior of the board will become a source of infection. In that respect, therefore, motivation to combine for these stated purposes is found in the Applicant's disclosure as a template for a hindsight reconstruction based on the three references applied.

**Applicant's Declaration under 37 C.F. R. 1.131**

The examiner had held that the declaration was insufficient for the reasons noted on pages 4 and 5 of the Final Action, while at the same time asking for another copy of Exhibits A and B. To the extent that the file of the undersigned does not contain Exhibits apparently marked as Exhibits A and B as referred to therein. To resolve any question on that point, the following papers are presented from the file of the undersigned and correlated with the declaration of the Applicant.

1. Exhibit C to this submission consists of four pages of drawings made from a large drawing in the possession of the undersigned. It is believed that this drawing constituted Exhibit A to the Declaration. The undersigned confirms that it bears a date earlier than Richmond's effective filing date, assuming that it is entitled to its provisional filing date, and bears the legend "Revised Tail" having a date earlier than Richmond's effective filing date. The original drawing is available for an interview with the examiner to satisfy him that the dates contained thereon are indeed earlier than Richmond's effective filing date.

2. Exhibit D to this submission is believed to be the "written description" contained in Exhibit B to the Rule 131 Declaration. It has appended thereto drawings that accompanied that writeup, among which were the downwardly directed tail section. It is noted that at least several of those drawings, apparently provided to prepare the provisional application bear a date of April 29, 2002, a date that is earlier than the effective filing date of the Richmond citation. Exhibit D is a writeup from the Applicant of the main points to be considered for inclusion in the provisional application filed in July, 2002 on behalf of the Applicant. A date on the second page of the writeup is earlier than the effective filing date of the Richmond citation. It may be noted that the comment that the design would be available in the fall of 2000 is inaccurate to the extent that the design was developed to what is shown in the provisional application.

Richmond's Provisional Disclosure

A copy of the provisional application for the Richmond citation is provided. It is clear that Richmond relates to a stretcher, not a spineboard as claimed and does not contemplate or suggest the pathogen resistant feature of the Applicant's invention. To the extent that Richmond is entitled to rely on its provisional filing date, the Applicant needs only show so much of the Richmond case as is shown in its provisional case to antedate the disclosure completely. Richmond's provisional disclosure is thus antedated by the Applicant's activities.

To the extent that the undersigned reviewed files kept in the ordinary course of business to provide this response on documents supporting the declaration, the information submitted herein is true and accurate to the extent so stated, or is believed to be true and accurate to the best of the information of the undersigned.

These documents are believed to respond favorably to the points raised by the examiner who apparently did not have either Exhibit A or B before him in the file when criticizing the declaration.

Information Disclosure Statement

An Information Disclosure Statement accompanies this submission to present documents cited in the corresponding EP application and a copy of the action in that case for consideration by the Examiner.

Reconsideration is respectfully requested.

Dated: August 22, 2006

Respectfully submitted,

By 

Ronald P. Kananen

Registration No.: 24,104

RADER, FISHMAN & GRAUER PLLC

1233 20th Street, N.W.

Suite 501

Washington, DC 20036

(202) 955-3750


Attorney for Applicant

Attachment:

APPENDIXES (C), (D), and (E)

## **APPENDIX C**

*George Stanton*




BEST AVAILABLE COPY


# BEST AVAILABLE COPY

SCALE  $\frac{1}{2}$  cm = 1"  
1 cm = 2"

DRAWINGS BY GEORGE S. PANTON JR



BEST AVAILABLE COPY




Original  
DRAWING BY GEORGE S. PANTON JR

REVISED TAIL  
PLAN

BEST AVAILABLE COPY





Overall Thickness @ 2 1/4"

## **APPENDIX D**

## EXTREME RESPONSE

P.O. Box 372520  
SATELLITE BEACH, FLA  
32937

PHYSICAL ADDRESS  
128 TOMAHAWK DR. Suite C  
INDIAN HARBOR BCH. FLA  
32937

# MAXx

MAXx is a rescue backboard used for immobilization of injured persons resulting from accidents, spinal in nature.

The MAXx backboard is designed with many emergency issues relating to aquatic, EMS, or firefighters situations minimizing the rescue time at the "scene".

### MAXx Design FEATURES ARE:

1. The MOST X-rayable backboard with no metal parts or pieces
2. VACUUM formed of Thermal plastic being ultra strong and capable of heavy weight capacities
3. Urethane foam filled ... eliminates air SPACES
4. Blood born pathogen resistant - ~~is~~ impervious structure with sealed edges
5. Moulded in Speed clip pins
6. Shot pinned hand holes for superior grip
7. Adjustable head immobilizer - can be pediatric or adult
8. Tipped down tail for quicker extrication of Auto accident patients
9. Bottom runners for aquatic rescues and/or ground stabilization
10. Light weight

## Introducing the "MAXx" Backboard - Patent Details and Description

Protocol, ease of use/buoyancy in the water, bloodbourne pathogen procedures, EMS specifications, and technological advances have been the design paramaters leading to the backboard of the future-- "MAXx"

Designed by George Panton, "MAXx" features a revolutionary adjustable "snap-set" head immobilizing system.

Stability, positive buoyancy, rigidity, sterility, density, and strength have all been addressed to maximize the performance of "MAXx" within the EMS and the aquatic market.

This patent-pending design will be available in the Fall of 2000. This product is a "purpose" built backboard that is unique among any previous designs.


*Mr. J. J. J. J.*

### Features:






- Lightweight polyethylene/poly urethane foam core or ABS
- X-ray translucent
- Integrated design will accommodate snap-in Head Immobilizers
- Maximum human weight limit consistent with strap length maximums
- Larger handholds for greater vertical strap adjustment and safety glove clearance
- Unique dropped tail design allows easier board placement/extrication out of pools, tight spots (i.e. car seats, etc).
- Unique ~~tail~~ shaped tail handles allow easy grasp when flat to the ground or on pool edge
- Side handles are "shot pinned" to facilitate wet (aquatic) rescues
- Deck cradle is smooth for additional comfort
- ~~Fiberglass speed clip~~ pins
- Private label capability
- International Orange in color

Submitted by George Panton Jr.






BEST AVAILABLE COPY




BEST AVAILABLE COPY



BACKUP  
MAIN MENU  
-PM-  
Z: 4.4918  
Color:   
Level: 9  
Style/Width  
Mask: OFF  
Tplane: OFF  
Cplane: T  
Gview: T









Main Menu:

Analyze

Create

File

Modify

Xform

Delete

Screen

Toolpaths

NC utils

Exit

BACKUP

MAIN MENU

PM

Z: 4.4916

Color: 13

Level: 9


Style/Width

Mask: OFF


Plane: OFF

Cplane: 3D

View: M



X  
Y



Drafting:

Dimension

Note

Label

Leader

Witness

Quick edit

Globals edit

Text edit

Hatch

BACKUP

MAIN MENU

PM

Z: 4.4918

Color: 2

Level: 9


Style/Width

Mask: OFF


Tplane:OFF

Cplane: F


Gview: F




BEST AVAILABLE COPY




BEST AVAILABLE COPY



BEST AVAILABLE COPY





BEST AVAILABLE COPY



BEST AVAILABLE COPY

16 x 5"  
LOGO SPACE for  
MAXx or Custom LOGO



BEST AVAILABLE COPY

## **APPENDIX E**



FILE WRAPPER FOR PROVISIONAL U.S. APPLICATION

NO: 60/380,715  
INVENTOR: THOMAS A. RICHMOND  
FILING DATE: MAY 15, 2002  
TITLE: STRETCHER

---

\*RELATED U.S. APPLICATION DATA:

USSN 10/404,814 FILED APRIL 1, 2003  
US PATENT 6,715,170

PROVISIONAL APPLICATION NO. 60/380,715  
FILED MAY 15, 2002 [CAPTIONED FILE]

\*The related U.S. application data is drawn from the USPTO's public website and is not to be construed as a complete family of applications. Complete family information is available from the USPTO under 37 CFR 1.14.

---

60380715  
60380715

J1040 U.S. PTO  
60/380715  
05/15/02

AK-7

001

1.

2. PDA 7/19/02  
3. PDA NOTICE 2/28/02  
4. Request for access 6/10/04



## UNITED STATES PATENT AND TRADEMARK OFFICE


COMMISSIONER FOR PATENTS  
UNITED STATES PATENT AND TRADEMARK OFFICE  
WASHINGTON, D.C. 20231  
www.uspto.gov



Bib Data Sheet

CONFIRMATION NO. 6839

<b>SERIAL NUMBER</b> 60/380,715	<b>FILING DATE</b> 05/15/2002 <b>RULE</b>	<b>CLASS</b>	<b>GROUP ART UNIT</b>	<b>ATTORNEY DOCKET NO.</b> RAPI-0003
<b>APPLICANTS</b> Thomas A. Richmond, Richboro, PA;				
<b>** CONTINUING DATA *****</b>				
<b>** FOREIGN APPLICATIONS *****</b>				
<b>IF REQUIRED, FOREIGN FILING LICENSE GRANTED** SMALL ENTITY **</b> ** 06/17/2002				
Foreign Priority claimed <input type="checkbox"/> yes <input type="checkbox"/> no	35 USC 119 (a-d) conditions met <input type="checkbox"/> yes <input type="checkbox"/> no <input type="checkbox"/> Met after Allowance	<b>STATE OR COUNTRY</b> PA	<b>SHEETS DRAWING</b> 5	<b>TOTAL CLAIMS</b>
Verified and Acknowledged	Examiner's Signature _____ Initials _____			<b>INDEPENDENT CLAIMS</b>
<b>ADDRESS</b> Andrew J. Hagerty WOODCOCK WASHBURN LLP One Liberty Place - 46th Floor Philadelphia, PA 19103				
<b>TITLE</b> Stretcher				
<b>FILING FEE RECEIVED</b> 80	FEES: Authority has been given in Paper No. _____ to charge/credit DEPOSIT ACCOUNT No. _____ for following:		<input type="checkbox"/> All Fees <input type="checkbox"/> 1.16 Fees ( Filing ) <input type="checkbox"/> 1.17 Fees ( Processing Ext. of time ) <input type="checkbox"/> 1.18 Fees ( Issue ) <input type="checkbox"/> Other _____ <input type="checkbox"/> Credit	



J1040 U.S. PTO  
60/380715



AK-1

AK-1

- 1.
2. PDA 7/19/02
3. PDA NOTICE 7/30/02
4. Request for allers 6/10/04

BEST AVAILABLE COPY

PROVISIONAL APPLICATION COVER SHEET

Request for filing a PROVISIONAL APPLICATION under 37 CFR 1.53(c).

05/15/02  
3108 U.S. PAT. & TM. OFF. MAIL LABEL NO. 15587AUS  
OFFICE OF DEPOSIT: MAY 15, 2002

EL928558187US

Docket Number: RAPI-0003

Type a plus sign  
(+) inside this  
box-

+

INVENTOR(S)/APPLICANT(S)

GIVEN NAME  
(FIRST AND MIDDLE [IF ANY])

FAMILY NAME OR  
SURNAME

RESIDENCE (CITY AND EITHER STATE OR  
FOREIGN COUNTRY)

Thomas A.

Richmond

7 Titus Avenue  
Richboro, Pennsylvania 18954

☐ Additional inventors are being named on the \_\_\_\_\_ separately numbered sheets attached hereto

TITLE OF THE INVENTION (280 characters max)

STRETCHER

CORRESPONDENCE ADDRESS

Attorney Name: Andrew J. Hagerty  
WOODCOCK WASHBURN LLP  
One Liberty Place - 46th Floor  
Philadelphia PA 19103  
Telephone (215) 568-3100  
Facsimile (215) 568-3439

ENCLOSED APPLICATION PARTS (check all that apply)

☒ Specification  
☒ Drawing(s)

Number of Pages 10  
Number of Sheets 5

43  
Claims (optional)  
Other (specify) \_\_\_\_\_

METHOD OF PAYMENT (check one)

☒ A check or money order is enclosed to cover the Provisional filing fee:

☒ \$80.00 Small Entity  
☐ \$160.00 Large Entity

☐ The Commissioner is hereby authorized to charge filing fee and credit Deposit Account Number: 23-3050

☒ The Commissioner is hereby authorized to charge Deposit Account 23-3050 any fee deficiency or credit account for any overpayment.

This invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.

☒ No.

☐ Yes, the name of the U.S. Government agency and the Government contract number are: \_\_\_\_\_

Respectfully submitted,

SIGNATURE

TYPED or PRINTED NAME Andrew J. Hagerty

Date: May 15, 2002  
REGISTRATION NO. 44,141  
(if appropriate)

PROVISIONAL APPLICATION FILING ONLY

STRETCHER

## FIELD OF THE INVENTION

5 The present invention relates to portable stretchers, which are particularly suited for rescue situations. The stretchers are effective in transporting patients and/or rescuers in environments including water, ice and snow.

## BACKGROUND OF THE INVENTION

## 10 SUMMARY OF THE INVENTION

60380715-051502 15 The present invention is directed to stretchers. In accordance with one preferred embodiment of the present invention, there has now been provided a stretcher including a cavity defined by a base and at least one wall extending upwardly from the periphery of the base. The cavity includes a pair of runners disposed on its lower surface. The cavity is formed having a double-wall configuration with filler material therebetween. The stretcher is floatable with a load of about 200 pounds residing in the cavity in the absence of retrofitted flotation aids.

20 In accordance with another preferred embodiment, there has now been provided a stretcher including a substantially rigid cavity for protecting a patient, wherein the cavity is defined by a base, longitudinal ends extending upwardly from the base, and sidewalls disposed between the longitudinal ends and extending upwardly the base. The sidewalls extend to a varying elevation along the lengths of the sidewalls.

25 In accordance with another preferred embodiment, there has now been provided a stretcher including a cavity defined by a base and at least one wall extending upwardly from the periphery of the base. A pair of runners is disposed on a lower surface of the cavity. The cavity wall includes opposing notches so that human limbs can be extended out of the cavity to maneuver the stretcher.

30 In accordance with another preferred embodiment, there has now been provided a stretcher including a cavity defined by a base and at least one wall extending upwardly from the periphery of said base. The cavity wall extends to a varying elevation along its length. The cavity is formed having a double-wall configuration with filler material

therebetween. The stretcher is floatable with a load of about 200 pounds residing in the cavity in the absence of retrofitted flotation aids.

These and various other features of novelty, and their respective advantages, are pointed out with particularity in the claims annexed hereto and forming a part hereof.

5 However, for a better understanding of aspects of the invention, reference should be made to the drawings which form a further part hereof, and to the accompanying descriptive matter, in which there is illustrated preferred embodiments.

#### BRIEF DESCRIPTION OF THE DRAWINGS

10 Figure 1 is a top perspective view of a preferred stretcher embodiment provided by the present invention.

Figure 2 is a top perspective view of another preferred embodiment provided by the present invention.

15 Figure 3 is a top perspective view of a stretcher embodiment including optional drain ports.

Figure 4 is bottom perspective view of a stretcher embodiment including optional runners.

20 Figure 5 is a top perspective view of the stretcher embodiment as shown in Figure 4.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the figures, wherein like features are indicated with like reference characters throughout, and in particular to Figure 1, a stretcher 10 is shown including a cavity 20 that is defined by a base 30, sidewalls 32, and longitudinal ends 33.

25 The stretcher embodiments shown in these figures have distinct wall portions joined at their ends, and the walls are substantially linear. As can be seen in Figure 2 however, other stretcher embodiments according to the present invention may include a single wall 31 (that is, not having distinct starting and ending points) positioned at the periphery of base 30 and extending upwardly therefrom. Figure 2 also illustrates that any wall or wall

30 portion may include curvilinear regions.

Referring again to Figure 1, cavity 20 and base 30 are designed and configured to accept a patient and/or rescuer directly, or alternatively accept a patient positioned on an immobilization board. Cavity 20 is preferably substantially rigid so that a patient can be adequately protected during transportation.

5 In preferred stretcher embodiments, stretcher walls (wall 31 and sidewalls 32) extend to a varying elevation along their lengths, with low sections that permit a rescuer to extend their arms and/or legs out of cavity 20 to maneuver the stretcher, including propelling, braking and steering the stretcher during patient search and rescue. For example, in a water rescue, a rescuer can use the stretcher as a flotation aid and paddle out to a victim. Similarly, in an ice rescue, a rescuer can extend their arms or legs out to pick their way along the ice. Stretcher walls include regions with a relatively high elevation E1 and other regions with a relatively low elevation E2 (more than two different elevations may be employed). Elevation E1 is preferably from about 3 inches to about 18 inches. Elevation E2 is preferably from about 1 inch to about 10 inches.

10 15 The stretcher embodiments shown in the figures include notches 40 in the sidewalls to provide low sections. Although a single pair of opposing notches is suitable for effectively enabling a rescuer to maneuver the stretcher, two pairs of opposing notches 40 are preferred. When two pairs of opposing notches 40 are employed, a rescuers arms and legs can be extended out of the cavity. In addition, two pairs of  
20 opposing notches allow a rescuer to quickly grasp the stretcher without orientation concerns. For example, a rescuer could be positioned in either direction in the cavity and extend their arms out to paddle the stretcher through the water.

Sidewalls 32 and ends 33 are shown having an optional outwardly extending flange 41. Preferably, flange 41 is substantially parallel to base 30. In preferred  
25 embodiments, flange 41 includes at least one opening. As shown, flange 41 has multiple openings, including several hand holes 42 and strap holes 43. Strap holes 43 facilitate the attachment of restraining/securing straps, bridles and the like. Hand holes 42 and strap holes 43 may optionally contain speed pins 44, which provide quick-release coupling of a strap (or the like) via standard clips. Flange 41 may also include a seat for securing an  
30 oxygen bottle to the stretcher. A preferred bottle seat includes a concavity formed in a



portion of flange 41 and at least one coupling device to maintain the bottle's position within the concavity.

Referring to Figure 3, base 30 may optionally include at least one pluggable drain port 50. A plurality of spaced apart ports 50 is preferred. The pluggable drain ports enable stretchers of the present invention to be used for decontaminating a patient. For example, a patient exposed to hazardous material can be "washed" while lying in the stretcher. The runoff can then be safely contained by routing it out of the drain ports and into a hazardous material disposal container. Blood and other bodily fluids can likewise be appropriately handled via the ports when the stretcher is cleaned and sanitized post use. The drain ports may also be used for introducing materials into the cavity, such as, for example, heated air or medicaments.

Stretchers of the present invention may employ runners to provide enhanced maneuverability and tracking in water and snow use. The runners can be manufactured independently and then attached to the stretcher, or integrally formed with the stretcher cavity. As can be seen in Figure 4, two runners 60 extend from a bottom surface of cavity 20. In addition to the runners, the bottom surface of base 30 and ends 33 can be angled or shaped to promote the ability of the stretcher to plow through water or snow.

The stretcher cavity can be manufactured from many different materials, including but not limited to, polymers, metals, composites, foams, fiberglass, wood, KEVLAR, coated paperboard, and combinations thereof. Preferably, the stretcher is made from a material comprising a polymer, such as, for example high-density polyethylene. Any known techniques for forming three-dimensional structures from the list of materials above can be employed for manufacturing the stretcher components.

In preferred embodiments, the cavity is injection molded or rotational molded. Utilizing a rotational molding technique can yield a hollow double-wall configuration. Filler material may be disposed in the middle of such a configuration to impart added strength, and insulation and flotation properties. A representative, non-limiting list of filler material includes air, foam, natural and synthetic fibers, and wood products. Preferably, the filler material is a liquid foam, such as catalyzed urethane foam, that is injected into the double-wall configuration with techniques such as reaction injection molding.

Design features, materials, and manufacturing techniques as described above may be selectively combined to provide various beneficial properties, such as, for example, x-ray translucency and floatation. Stretchers of the present invention are preferably floatable, more preferably floatable with a load of about 200 pounds residing in the cavity, and most preferably floatable containing a load of up to about 350 pounds, all in the absence of retrofitted (additional) flotation aids.

It is to be understood that even though numerous characteristics and advantages of the present invention have been set forth in the foregoing description, together with details of the structure, manufacture of, and function of the invention, the disclosure is illustrative only. Accordingly, changes may be made in detail, especially in matters of shape, size and arrangement of structural features, as well as, sequences of manufacturing steps, within the principles of the invention to the full extent indicated by the broad general meaning of the terms in which the appended claims are expressed.

60380715-051502

What is claimed is:

- 60380715-051502
1. A stretcher comprising:  
5 a cavity defined by a base and at least one wall extending upwardly from the periphery of said base; and  
a pair of runners disposed on a lower surface of said cavity;  
wherein said cavity is formed having a double-wall configuration with filler material therebetween, so that the stretcher is floatable with a load of about 200 pounds  
10 residing in said cavity in the absence of retrofitted flotation aids.
  2. The stretcher of claim 1, wherein said cavity and said pair of runners are integrally formed.
  - 15 3. The stretcher of claim 1, wherein at least a portion of said at least one wall includes an outwardly extending flange that is substantially parallel to said base.
  4. The stretcher of claim 3, wherein said flange includes an opening.
  - 20 5. The stretcher of claim 4, wherein said opening is a hand hole.
  6. The stretcher of claim 4, wherein said opening includes a pin for attaching a bridle or a securing strap to the stretcher.
  - 25 7. The stretcher of claim 3, wherein said flange includes a bottle seat.
  8. The stretcher of claim 1, wherein said base includes at least one pluggable drain port extending from a base upper surface to a base lower surface.
  - 30 9. The stretcher of claim 1, wherein said cavity is formed by a manufacturing method including rotational molding.

50380715-051502

10. The stretcher of claim 1, wherein said cavity is formed from a material including a polymer.
- 5 11. The stretcher of claim 10, wherein said polymer includes a high-density polyethylene.
12. The stretcher of claim 1, wherein said filler material includes foam.
- 10 13. The stretcher of claim 1, wherein said cavity is sized and configured to accept an immobilization board.
14. The stretcher of claim 1, wherein said cavity is x-ray translucent.
- 15 15. The stretcher of claim 1, wherein said at least one wall includes two sidewalls positioned between two opposing ends.
16. The stretcher of claim 15, wherein each of said two sidewalls includes a region of relatively low elevation so that a human limb can be extended out of said cavity to  
20 maneuver the stretcher.
17. A stretcher comprising:  
a substantially rigid cavity for protecting a patient, the cavity defined by a base, longitudinal ends extending upwardly from said base, and sidewalls disposed between  
25 said longitudinal ends and extending upwardly from said base;  
wherein said sidewalls extend to a varying elevation along the lengths of said sidewalls.
18. The stretcher of claim 17, further comprising a pair of runners disposed on a  
30 lower surface of said cavity.

19. The stretcher of claim 17, wherein at least one of said sidewalls and said longitudinal ends include an outwardly extending flange that is substantially parallel to said base.

5 20. The stretcher of claim 19, wherein said flange includes an opening for accepting a lifting or securing device.

21. The stretcher of claim 19, wherein said flange includes a bottle seat.

10 22. The stretcher of claim 17, wherein said base includes at least one pluggable drain port extending from a base upper surface to a base lower surface.

23. The stretcher of claim 17, wherein said cavity is formed by a manufacturing method including rotational molding.

15 24. The stretcher of claim 17, wherein said cavity is formed having a double-wall configuration with filler material therebetween.

20 25. The stretcher of claim 24, wherein said filler material includes foam.

26. The stretcher of claim 17, wherein said cavity is formed from a material including a polymer.

25 26. The stretcher of claim 26, wherein said polymer includes a high-density polyethylene.

27. The stretcher of claim 17, wherein said cavity is sized and configured to accept an immobilization board.

30 28. The stretcher of claim 17, wherein said cavity is x-ray translucent.

60380715-051502

29. The stretcher of claim 17, wherein each of said sidewalls include a notch so that human limbs can be extended out of said cavity to maneuver the stretcher.

30. The stretcher of claim 28, wherein each of said sidewalls includes a second notch.

31. A stretcher comprising:  
a cavity defined by a base and at least one wall extending upwardly from the periphery of said base; and  
a pair of runners disposed on a lower surface of said cavity;  
wherein said at least one wall includes opposing notches so that human limbs can be extended out of said cavity to maneuver the stretcher.

32. The stretcher of claim 31, wherein at least a portion of said at least one wall includes an outwardly extending flange that is substantially parallel to said base.

33. The stretcher of claim 32, wherein said flange includes an opening for accepting a lifting or securing device.

34. The stretcher of claim 32, wherein said flange includes a bottle seat.

35. The stretcher of claim 31, wherein said base includes at least one pluggable drain port extending from a base upper surface to a base lower surface.

36. The stretcher of claim 31, wherein said cavity is formed by a manufacturing method including rotational molding.

37. The stretcher of claim 31, wherein said cavity is formed having a double-wall configuration with filler material therebetween.

38. The stretcher of claim 37, wherein said fill materials includes foam.

39. The stretcher of claim 31, wherein said cavity is formed from a material including a polymer.

40. The stretcher of claim 39, wherein said polymer includes a high-density polyethylene.

41. The stretcher of claim 31, wherein said cavity is sized and configured to accept an immobilization board.

42. A stretcher comprising:  
a cavity defined by a base and at least one wall extending upwardly from the periphery of said base;  
wherein said at least one wall extends to a varying elevation along its length, and  
wherein said cavity is formed having a double-wall configuration with filler material therebetween, so that the stretcher is floatable with a load of about 200 pounds residing in said cavity in the absence of retrofitted flotation aids.

43. The stretcher of claim 42 being floatable with a load up to about 350 pounds residing in said cavity in the absence of flotation aids.

60380715.051502

60380715.051502




FIG. 1

BEST AVAILABLE COPY



60380715.051502





FIG. 2

BEST AVAILABLE COPY



BEST AVAILABLE COPY

60380715.051502





FIG. 4

BEST AVAILABLE COPY



BEST AVAILABLE COPY



DOCKET NO. RAFF-0003

92201  
PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Application of:  
THOMAS A. RICHMOND

Serial No.: 60/380,715

Filed: May 15, 2002

For: STRETCHER

COPY OF PAPERS  
ORIGINALLY FILED

BOX PROVISIONAL PATENT APPLICATION

Assistant Commissioner for Patents  
Washington, DC 20231

Sir:

POWER OF ATTORNEY FOR PROVISIONAL APPLICATION

The undersigned hereby appoints the following attorneys and/or agents of the firm  
WOODCOCK WASHBURN LLP, One Liberty Place - 46th Floor, Philadelphia, Pennsylvania  
19103 to prosecute this application and to transact all business in the Patent and Trademark  
Office connected therewith:

Richard E. Kurtz	Registration No. 19,263	Janet E. Reed	Registration No. 36,252
Dale M. Heist	Registration No. 28,425	Jeffrey J. King	Registration No. 38,515
John W. Caldwell	Registration No. 28,937	Robert B. Washburn	Registration No. 16,574
Gary H. Levin	Registration No. 28,734	Norman L. Norris	Registration No. 24,196
Steven J. Rocci	Registration No. 30,489	Michael J. Swope	Registration No. 38,041
Dianne B. Elderkin	Registration No. 28,598	Michael J. Bonella	Registration No. 41,628
John P. Donohue, Jr.	Registration No. 29,916	Harold H. Fullmer	Registration No. 42,560
Henrik D. Parker	Registration No. 31,863	John E. McGlynn	Registration No. 42,863
Suzanne E. Miller	Registration No. 32,279	Jonathan M. Waldman	Registration No. 40,861
Lynn B. Morreale	Registration No. 32,842	Chad Ziegler	Registration No. 44,273
Mark DeLuca	Registration No. 33,229	Gwilym J.O. Attwell	Registration No. 45,449
Joseph Lucci	Registration No. 33,307	David N. Farsiou	Registration No. 44,104
Michael P. Dunnam	Registration No. 32,611	Paul K. Legaard	Registration No. 38,534
Michael D. Stein	Registration No. 34,734	Steven H. Meyer	Registration No. 37,189
Albert J. Marcellino	Registration No. 34,664	Paul B. Milcetic	Registration No. 46,261
David R. Bailey	Registration No. 35,057	Joseph R. Condo	Registration No. 42,431
Doreen Yatko Trujillo	Registration No. 35,719	Michael K. Jones	Registration No. 41,100
Barbara L. Mullin	Registration No. 38,250	Frank T. Carroll	Registration No. 42,392
Michael P. Straher	Registration No. 38,325	Thomas E. Watson	Registration No. 43,243
Kevin M. Flannery	Registration No. 35,871	Peter M. Ullman	Registration No. 43,963
David A. Cherry	Registration No. 35,099	Richard B. LeBlanc	Registration No. 39,495
Lynn A. Malinoski	Registration No. 38,788	Joseph D. Rossi	Registration No. 47,038
Steven B. Samuels	Registration No. 37,711	George J. Awad	Registration No. 46,528

DOCKET NO. RAPI-0003

- 2 -

PATENT

Steven D. Maslowski	Registration No. 46,905	Richard D. Watkins	Registration No. P50,993
S. Maurice Valla	Registration No. 43,966	Wendy A. Choi	Registration No. 36,697
Emma R. Dailey	Registration No. 48,491	Felicity E. Groth	Registration No. 47,042
Vincent J. Roccia	Registration No. 43,887	Christine A. Goddard	Registration No. 46,731
Patrick J. Farley	Registration No. 42,524	Andrew J. Hagerty	Registration No. 44,141
Stephen C. Timmins	Registration No. 48,481	Scott E. Scioli	Registration No. 47,930
Erich M. Falke	Registration No. 49,049		
Jane E. Inglese	Registration No. 48,444		
Susan C. Murphy	Registration No. 46,221		
Raymond N. Scott, Jr.	Registration No. 48,666		
David L. Marcus	Registration No. 46,897		
Lawrence A. Aaronson	Registration No. 38,369		
John A. Harrelson	Registration No. 42,637		
Sharon Fenick	Registration No. 45,269		
Daniel D. Biesterveld	Registration No. 45,898		
Phillip A. Singer	Registration No. 40,176		

and requests that correspondence continue to be directed to the firm of WOODCOCK  
WASHBURN LLP at the above address and telephone calls be directed to (215) 568-3100.

Date: 6-20-02

Inventor: Thomas A. Richmond  
Type Name: THOMAS A. RICHMOND



Commissioner for Patents  
Washington, DC 20231  
www.uspto.gov

APPLICATION NUMBER	FILING DATE	FIRST NAMED APPLICANT	ATTY. DOCKET NO./TITLE
60/380,715	05/15/2002	Thomas A. Richmond	RAPI-0003

Andrew J. Hagerty  
WOODCOCK WASHBURN LLP  
One Liberty Place - 46th Floor  
Philadelphia, PA 19103

CONFIRMATION NO. 6839



\*OC000000008873050\*

Date Mailed: 09/30/2002

### NOTICE OF ACCEPTANCE OF POWER OF ATTORNEY

This is in response to the Power of Attorney filed 07/19/2002.


The Power of Attorney in this application is accepted. Correspondence in this application will be mailed to the above address as provided by 37 CFR 1.33.

ELISHA M EVANS  
OPE (703) 306-3493

OFFICE COPY

REQUEST FOR ACCESS TO AN ABANDONED APPLICATION UNDER 37 CFR 1.14

Bring completed form to:  
File Information Unit  
Crystal Plaza Three, Room 1D01  
2021 South Clark Place  
Arlington, VA  
Telephone: (703) 308-2733



In re Application of

Application Number

Filed

601580,715

05-15-02

Paper No. #4

I hereby request access under 37 CFR 1.14(a)(1)(iv) to the application file record of the above-identified ABANDONED application, which is identified in, or to which a benefit is claimed, in the following document (as shown in the attachment):

United States Patent Application Publication No. \_\_\_\_\_, page, \_\_\_\_\_ line \_\_\_\_\_.

United States Patent Number US 6,715,170 B2, column \_\_\_\_\_, line, \_\_\_\_\_ or \_\_\_\_\_.

WIPO Pub. No. \_\_\_\_\_, page \_\_\_\_\_, line \_\_\_\_\_.

**Related Information about Access to Pending Applications (37 CFR 1.14):**

Direct access to pending applications is not available to the public (see 37 CFR 1.14(c) if applicant) but copies may be available and may be purchased from the Office of Public Records upon payment of the appropriate fee (37 CFR 1.19(b)), as follows:

**For published applications that are still pending**, a member of the public may obtain a copy of:

- the file contents;
- the pending application as originally filed; or
- any document in the file of the pending application.

**For unpublished applications that are still pending:**

- (1) If the benefit of the pending application is claimed under 35 U.S.C. 119(e), 120, 121, or 365 in another application that has: (a) issued as a U.S. patent, or (b) published as a statutory invention registration, a U.S. patent application publication, or an international patent application publication in accordance with PCT Article 21(2), a member of the public may obtain a copy of:
  - the file contents;
  - the pending application as originally filed; or
  - any document in the file of the pending application.
- (2) If the application is incorporated by reference or otherwise identified in a U.S. patent, a statutory invention registration, a U.S. patent application publication, or an international patent application publication in accordance with PCT Article 21(2), a member of the public may obtain a copy of:
  - the pending application as originally filed.

*Rachel Haul*

Signature

*Rachel Haul*

Typed or printed name

Registration Number, if applicable

703-486-1150

Telephone Number

06-10-04

Date

FOR PTO USE ONLY

Approved by: *J. Bryant*

RECEIVED

Unit:

JUN 10 2004

This collection of information is required by 37 CFR 1.14. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual's circumstances. Comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. BRING TO: File Information Unit, Crystal Plaza Three, Room 1D01, 2021 South Clark Place, Arlington, VA.  
If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.





US006715170B2

(12) **United States Patent**  
Richmond

(10) Patent No.: **US 6,715,170 B2**  
(45) Date of Patent: **Apr. 6, 2004**

(54) **STRETCHER**

(75) Inventor: **Thomas A. Richmond, 7 Titus Ave.,  
Richboro, PA (US) 18954**

(73) Assignee: **Thomas A. Richmond, Richboro, PA  
(US)**

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/404,814**

(22) Filed: **Apr. 1, 2003**

(65) **Prior Publication Data**

US 2003/0213066 A1 Nov. 20, 2003

**Related U.S. Application Data**

(60) Provisional application No. 60/380,715, filed on May 15,  
2002

(51) Int. Cl.<sup>7</sup> ..... **A61G 1/00**

(52) U.S. Cl. .... **5/625; 5/626; 5/628; 128/870;  
441/129**

(58) Field of Search ..... **5/625, 626, 628;  
441/83, 125, 129; 128/870**

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,033,000 A \* 7/1977 Bonifay ..... 5/628  
4,183,110 A \* 1/1980 Kidd et al. .... 5/629  
5,190,056 A \* 3/1993 Hull ..... 5/621  
5,473,784 A \* 12/1995 Nixon et al. .... 5/625

5,749,374 A \* 5/1998 Schneider, Sr. .... 128/870  
5,765,243 A \* 6/1998 Duncan et al. .... 5/625  
5,950,627 A 9/1999 Bologovsky et al. .... 128/869  
6,073,287 A \* 6/2000 Svensson ..... 5/625  
6,352,460 B1 \* 3/2002 Eiband et al. .... 441/80

**FOREIGN PATENT DOCUMENTS**

GB 2143138 A \* 2/1985  
GB 2182570 A \* 5/1987

**OTHER PUBLICATIONS**

Rapid Deployment Products, Inc., <http://www.prolitespine-boards.com>, 33 pages, Undated.

Skedco, Inc., Sked® Basic Rescue System, <http://www.emergencynet.com/sked/sk200.htm>, 5 pages, 1997.

Product Catalogue from BoundTree Medical Company, 2 pages, Undated.

Product Catalogue from Southeastern Emergency Equipment, pp. 5 and 6, Undated.

\* cited by examiner


Primary Examiner—Michael F. Trettel

(74) Attorney, Agent, or Firm—Woodcock Washburn LLP

(57) **ABSTRACT**

A stretcher including a substantially rigid cavity defined by a base, opposing ends extending upwardly from the base, and opposing sidewalls disposed between the opposing ends and extending upwardly from the base. Each of the opposing sidewalls includes at least one low section so that a human limb can be extended out of the cavity to maneuver the stretcher.

30 Claims, 7 Drawing Sheets



PATENT APPLICATION SERIAL NO. \_\_\_\_\_

U.S. DEPARTMENT OF COMMERCE  
PATENT AND TRADEMARK OFFICE  
FEE RECORD SHEET

05/20/2002 ZJUHR1 00000021 60380715

01 FC:214

80.00 DP

PTO-1556  
(5/87)